



AGAT CLEAN SLIGHT LED

Clean luminaires - recessed



Luminary designed to module suspended ceilings. Light distribution made by using high performance lenses. Luminary body made from steel sheet, powder coated in white. Luminary recommended for: emergency departments, intensive care units, and treatment rooms.




Cosmetics laboratory Dr Irena Eris, Piaseczno



Main parameters:

| Name | Luminous flux LED [lm] | Power of luminaire [W] | Color [K] | Dimensions A x B x H [mm] |
|----------------------------|------------------------|------------------------|-----------|---------------------------|
| AGAT CLEAN SLIGHT LED 2600 | 2617 | 14,4 | 4000 | 595 x 595 x 35 |
| AGAT CLEAN SLIGHT LED 3900 | 3926 | 21,7 | 4000 | 595 x 595 x 35 |
| AGAT CLEAN SLIGHT LED 4400 | 4565 | 24,7 | 4000 | 595 x 595 x 35 |
| AGAT CLEAN SLIGHT LED 5200 | 5234 | 28,2 | 4000 | 595 x 595 x 35 |
| AGAT CLEAN SLIGHT LED 6600 | 6848 | 35,3 | 4000 | 595 x 595 x 35 |
| AGAT CLEAN SLIGHT LED 8800 | 9130 | 49,1 | 4000 | 595 x 595 x 35 |

Technical drawing:



Light and electrical features:

| | |
|----------------------------------|---------------------------|
| Light source | LED |
| Voltage | 220..240 V, 50..60 Hz |
| Lifetime of LED sources [h] | 100000 (1) / 147000 (2) |
| Lx/By | L80/B10 (1) / L70/B50 (2) |
| CRI | >80 |
| SDCM (LED sources) | 3 |
| Operating temperature range [°C] | 5 ÷ 30 |
| Driver | standard on/off (E) |
| Power factor cos φ | >0,95 |

Mechanical features:

| | |
|----------|---------------------------------|
| Assembly | mounted in module ceilings |
| Material | steel sheet |
| Color | RAL 9016 (white) |
| Diffuser | SH (transparent hardened glass) |

Note: The power shown refers to the whole system (tolerance +/- 10%).
The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 24-01-2023