



METEOR LUX LED

Surface mounted luminaires



Surface mounted luminaires equipped with highly efficient LED sources. Luminary base made from powder coated steel sheet. Lampshade made from the opal version of methyl polymethacrylate. Luminary mounted directly on ceilings by raw plugs.




Environmental House of self-help, Białystok



Main parameters:

Name	Luminous flux LED [lm]	Power of luminaire [W]	Color [K]	Dimensions A x B x H [mm]
METEOR LUX LED 2600	2525 / 2617	14,4	3000 / 4000	1255 x 207 x 71
METEOR LUX LED 4400	4406 / 4565	24,7	3000 / 4000	1255 x 207 x 71
METEOR LUX LED 5200	5051 / 5234	28,2	3000 / 4000	1255 x 207 x 71
METEOR LUX LED 7200	6696 / 7200	48	3000 / 4000	1255 x 207 x 71
METEOR LUX LED 8800	8811 / 9130	49,1	3000 / 4000	1255 x 207 x 71

Technical drawing:



Light and electrical features:

Light source	LED
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)/60000
Lx/By	L80/B10 (1) / L70/B50 (2)/L80/B10
CRI	>80
SDCM (LED sources)	3
Photobiological risk class (IEC/EN 62471)	RG0
Operating temperature range [°C]	-25 ÷ 30
Driver	standard on/off (E) DIM DALI (EDD) *
Power factor cos φ	>0,95

* Variant to specify when ordering

Mechanical features:

Assembly	surface mounted on ceiling
Material	steel sheet
Color	white
Diffuser	PMMA opal

Additional information:

The luminaire can be made in CLO version.

Note: The power shown refers to the whole system (tolerance +/- 10%).
The given luminous flux refers to LED light sources (tolerance +/- 10% depends on the value of the colour temperature).
Technical data may be changed. Photos of the luminaires may differ from reality.
Date of last update: 24-01-2023