

Product: LAMINAR LED 1650 PC EDD 24 IP44 YELLOW MONO / L-859MM

Index: 0E1TDSL16YPC247D



Description

The luminaire has a streamlined, oval shape that makes the product suitable for use in rooms where laminar flow ventilation is used. This means that the air flowing around the luminaire or near it is less susceptible to mechanical resistance. The frosted shade is made of polycarbonate which is resistant to mechanical damage. The optical system ensures uniform illumination of the diffuser. Body made of anodized aluminium - available in aluminium color, optionally painted in other color required by the customer. High efficiency LED modules with color temperature 3000 K or 4000 K or LED modules with yellow light are used. Color rendering index at white light - CRI>80. Ceiling-mounted with springs, so that the luminaire does not need to be opened during installation. The standard luminaire is equipped with a 1 metre protruding cable for the connection, optionally the cable can be equipped with a connector or the connector (socket) can be installed in the side of the luminaire.

Product information


Category	Surface mounted luminaires
Family	LAMINAR LED
Name	LAMINAR LED 1650 PC EDD 24 IP44 YELLOW MONO / L-859MM
Index	0E1TDSL16YPC247D



Light and electrical data

Light source	LED
Luminous flux LED [lm]	1650
LED power [W]	39
Luminaire luminous flux [lm]	1293
Power of luminaire [W]	44
Luminaire's light efficiency [lm/W]	29,4
Color of the light [K]	yellow color (dominant wavelength $\lambda_p=592$ nm)
Beam angle [°]	(C0-C180) / (C90-C270) - 141,4° / 86,8°
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos ϕ	>0,95
Circuit load capacity	15 (B10), 24 (B16), 24(C10), 40 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	aluminum
Color	anodised aluminum
Diffuser	PC (opalcent polycarbonate)
Dimensions [mm]	859 x 47 x 109

A graph of light

