

**Product:** LUXWALL DECO LED 4X1,7W ODB-34 E 4000K

**Index:** 19.3022.0002.34



## Description

Architectural luminaire, wall mounted for decorative or accent lighting of representative interiors, halls or corridors. Eagerly used in such facilities as hotels, palaces, villas or art galleries. The body is made of steel painted white (RAL 9016). Other colors available upon special request. Luminaire reflector made of polished stainless steel (possibility of painting in white). The product is available in two variants due to the light source. It can be equipped with LED sources and an electronic driver or have a G9 base for interchangeable sources of general use that do not require a dedicated driver. In-direct luminaire.

## Product information

|          |  |
|----------|--|
| Category | Architectural luminaires               |
| Family   | LUXWALL DECO LED                       |
| Name     | LUXWALL DECO LED 4X1,7W ODB-34 E 4000K |
| Index    | 19.3022.0002.34                        |




## Light and electrical data

|                                     |  |
|-------------------------------------|--|
| Light source                        | LED                                      |
| Luminous flux LED [lm]              | 608                                      |
| LED power [W]                       | 5  |
| Luminaire luminous flux [lm]        | 296                                      |
| Power of luminaire [W]              | 10                                       |
| Luminaire's light efficiency [lm/W] | 29,6                                     |
| Color of the light [K]              | 4000                                     |
| CRI                                 | >80                                      |
| SDCM (LED sources)                  | 7  |
| Beam angle [°]                      | asymmetric light distribution            |
| Protection against electric shock   | I  |
| Protection degree                   | IP40                                     |
| Voltage                             | 220..240 V, 50..60 Hz                    |
| Lifetime of LED sources [h]         | 50000                                    |
| Lx/By                               | L70/B50                                  |
| Operating temperature range [°C]    | 5 ÷ 30                                   |
| Driver                              | standard on/off (E)                      |
| Power factor cos φ                  | >0,5                                     |
| Circuit load capacity               | 40 (B10), 78 (B16), 132 (C10), 158 (C16) |

## Mechanical data

|                  |                  |
|------------------|------------------|
| Assembly         | mounted on wall  |
| Material         | steel sheet      |
| Color            | RAL 9016 (white) |
| Diffuser         | none             |
| Impact resistant | IK02             |
| Weight [kg]      | 1,62             |
| Dimensions [mm]  | 260 x 103 x 220  |



## A graph of light

