

**Product:** AGAT LED 6500 MICRO-PRM EDD 840 / 600X600

**Index:** 19.3038.0178.34



## Description

Luminaire dedicated for module and suspended ceilings with the T24 grid, equipped with the highly efficient LED sources. Luminaire body made from steel sheet, powder coated in white. Monolithic construction is the characteristic feature of the luminaire (remaining in one-piece during exploitation process). Luminaire available in PLX or Micro-PRM diffuser. Luminaire dedicated for the public use structure.

## Product information

|          |  |
|----------|--|
| Category | <b>Recessed luminaires</b>                       |
| Family   | <b>AGAT LED</b>                                  |
| Name     | <b>AGAT LED 6500 MICRO-PRM EDD 840 / 600X600</b> |
| Index    | <b>19.3038.0178.34</b>                           |



## Light and electrical data


|   |   |
|---|---|
| Light source                              | <b>LED</b>                                    |
| Luminous flux LED [lm]                    | <b>6543</b>                                   |
| LED power [W]                             | <b>33,3</b>                                   |
| Luminaire luminous flux [lm]              | <b>5558</b>                                   |
| Power of luminaire [W]                    | <b>34,8</b>                                   |
| Luminaire's light efficiency [lm/W]       | <b>159,7</b>                                  |
| Color of the light [K]                    | <b>4000</b>                                   |
| CRI                                       | <b>&gt;80</b>                                 |
| SDCM (LED sources)                        | <b>3</b>                                      |
| Beam angle [°]                            | <b>(C0-C180) / (C90-C270) - 89° / 89°</b>     |
| Photobiological risk class (IEC/EN 62471) | <b>RG0</b>                                    |
| Protection against electric shock         | <b>I</b>                                      |
| Protection degree                         | <b>IP20/44</b>                                |
| Voltage                                   | <b>220..240 V, 50..60 Hz</b>                  |
| Lifetime of LED sources [h]               | <b>100000 (1) / 147000 (2)</b>                |
| Lx/By                                     | <b>L80/B10 (1) / L70/B50 (2)</b>              |
| Operating temperature range [°C]          | <b>5 ÷ 30</b>                                 |
| Driver                                    | <b>DIM DALI (EDD)</b>                         |
| Power factor cos φ                        | <b>&gt;0,95</b>                               |
| Circuit load capacity                     | <b>17 (B10), 28 (B16), 26 (C10), 41 (C16)</b> |

Mechanical data



|                  |   |
|------------------|---|
| Assembly         | mounted in module ceilings                |
| Material         | steel sheet                               |
| Color            | white                                     |
| Diffuser         | Micro-PRM (micro-prismatic diffuser PMMA) |
| Impact resistant | IK04                                      |
| Weight [kg]      | 5,6                                       |
| Dimensions [mm]  | 596 x 596 x 90                            |

A graph of light



Accessories

Index 2C1A7392-34R  
Name EUROPANEL / RIM COMPACT  
LED RECESSED ACCESSORIES  
34 / 600X600

