

Product: AGAT SLIM LED COMPACT 4000 PLX E 34 840**Index:** 19.3043.0133.34

Description

Luminary made from powder coated steel sheet. Highly efficient and power saving LED solutions have been used here (4000 lm of light stream, and color temperature of 4000 K). The product may be equipped with PMMA opal diffuser. Luminary dedicated for module ceilings, recommended to be used in public sectors such as offices, or conference rooms.

Product information


Category	Compact
Family	AGAT SLIM LED COMPACT
Name	AGAT SLIM LED COMPACT 4000 PLX E 34 840
Index	19.3043.0133.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	4118
LED power [W]	25
Luminaire luminous flux [lm]	3173
Power of luminaire [W]	27
Luminaire's light efficiency [lm/W]	117,5
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 101,2° / 103,2°
Protection against electric shock	I
Protection degree	IP20
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,64
Dimensions [mm]	591 x 115 x 88

A graph of light

