

**Product:** ARUNA LED 2R 8800M OPTICS-1L E 34 840 / 1200X300

**Index:** 19.3044.2202.34



## Description

LED luminaire dedicated to be mounted on suspended modular ceilings, cardboard suspended ceilings (using adaptive frame), directly on the ceiling (using ceiling slab) or using slings. Equipped with highly efficient LED light sources. Light distribution available with modern lenses. Housing made of steel sheet. Standard colour of the luminaire is white. Significant diversity of the value of luminous flux. Colour rendering index CRI: 80. Thanks to its innovative optics Aruna LED perfectly fits to be used in offices-especially to work with computers.

## Product information


|          |   |
|----------|---|
| Category | <b>Recessed luminaires</b>                              |
| Family   | <b>ARUNA LED</b>  |
| Name     | <b>ARUNA LED 2R 8800M OPTICS-1L E 34 840 / 1200X300</b> |
| Index    | <b>19.3044.2202.34</b>                                  |



## Light and electrical data


|                                     |  |
|-------------------------------------|--|
| Light source                        | <b>LED</b>                                     |
| Luminous flux LED [lm]              | <b>9288</b>                                    |
| LED power [W]                       | <b>50</b>                                      |
| Luminaire luminous flux [lm]        | <b>7414</b>                                    |
| Power of luminaire [W]              | <b>56</b>                                      |
| Luminaire's light efficiency [lm/W] | <b>132,4</b>                                   |
| Color of the light [K]              | <b>4000</b>                                    |
| CRI                                 | <b>&gt;80</b>                                  |
| SDCM (LED sources)                  | <b>3</b>                                       |
| Beam angle [°]                      | <b>(C0-C180) / (C90-C270) - 100,4° / 90,8°</b> |
| Protection against electric shock   | <b>I</b>                                       |
| Protection degree                   | <b>IP20</b>                                    |
| Voltage                             | <b>220..240 V, 50..60 Hz</b>                   |
| Lifetime of LED sources [h]         | <b>100000 (1) / 147000 (2)</b>                 |
| Lx/By                               | <b>L80/B10 (1) / L70/B50 (2)</b>               |
| Operating temperature range [°C]    | <b>5 ÷ 30</b>                                  |
| Driver                              | <b>standard on/off (E)</b>                     |
| Power factor cos φ                  | <b>&gt;0,95</b>                                |
| Circuit load capacity               | <b>15 (B10), 25 (B16), 24 (C10), 38 (C16)</b>  |

## Mechanical data



|                    |   |
|--------------------|---|
| Assembly           | <b>mounted in module ceilings, plasterboard ceilings, directly on the ceiling or using the slings</b> |
| Material           | <b>steel sheet</b>  |
| Color              | <b>RAL 9016 (white)</b>   |
| Diffuser           | <b>OPTICS (optical system based on lenses)</b>  |
| Impact resistant   | <b>IK04</b>   |
| Dimensions [mm]    | <b>1193 x 293 x 39</b>  |
| Mounting hole [mm] | <b>1210 x 310</b>   |


## A graph of light



## Accessories


Index 19.3044.0001.34

Name Frame for ceiling mounting /  
1200X300



Index 01ARNL-AGK120X30

Name Adaptive frame for plasterboard  
ceiling / 1200X300



Index 19.3272.0101.34

Name SUSPENSION NEW TYPE-G+H  
34 LENGHT 1,5M WIRE 3X SET  
TYPE-Y

