

Product: ONLINE LED 10400 PLX E 34 830 LINE-S / L-2400 Index: 19.3091.0040.34



Description


Luminary to be mounted on suspensions , or directly on solid ceiling construction. The suspended version is equipped with 1500 mm long suspension system that includes smooth regulation of the suspension length. Its body made from anodized aluminum profile. Luminary is equipped with highly efficient LED sources. Its diffuser is made from white polymethyl methacrylate with a light transparency more than 70%. Optical system creates Lambert diffuse reflection. No frame diffuser is equipped with specially formed latches that match the aluminum profile. Luminary is resistant to solids, dust, and humidity penetration – IP20.

| Product information | Category | Category Surface mounted luminaires | |
|---------------------------|---------------|---|---|
| | Family | ONLINE LED LINE | |
| | Name | ONLINE LED 10400 PLX E 34 830 LINE-S / L-2400 | |
| | Index | 19.3091.0040.34 | |
| | | | |
| Light and electrical data | Light source |) | LED |
| | Luminous fl | ux LED [lm] | 10102 |
| | LED power | [W] | 53,2 |
| | Luminaire Iu | uminous flux [lm] | 7970 |
| | Power of lur | minaire [W] | 56,3 |
| | Luminaire's | light efficiency [lm/W] | 141,6 |
| | Color of the | light [K] | 3000 |
| | CRI | | >80 |
| | SDCM (LED |) sources) | 3 |
| | Beam angle | e [°] | (C0-C180) / (C90-C270) - 93,8° / 96,6° |
| | Protection a | gainst electric shock | I |
| | Protection d | legree | IP20 |
| | Voltage | | 220240 V, 5060 Hz |
| | Lifetime of L | ED sources [h] | 100000 (1) / 147000 (2) |
| | Lx/By | | L80/B10 (1) / L70/B50 (2) |
| | Operating te | emperature range [°C |] 5 ÷ 30 |
| | Driver | | standard on/off (E) |
| | Power facto | r cos φ | >0,95 |
| | Circuit load | capacity | 16 (B10), 26 (B16), 23 (C10), 37 (C16) |
| Mechanical data | Assembly | | ectly mounted to ceiling construction or face mounted on slings |
| | Material | alu | minum |
| . <u> </u> | Color | RA | L 9016 (white) |
| | Diffuser | | X (PMMA opal) |
| | Impact resis | stant IKO | 4 |

Dimensions [mm]

2244 x 92 x 86


A graph of light



Accessories

Index 19.3272.0301.34

Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT




Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023