

Product: ONLINE LED 10400 PLX E 24 840 LINE-EP / L-2400 Index: 19.3091.0042.24



Description


Luminary to be mounted on suspensions , or directly on solid ceiling construction. The suspended version is equipped with 1500 mm long suspension system that includes smooth regulation of the suspension length. Its body made from anodized aluminum profile. Luminary is equipped with highly efficient LED sources. Its diffuser is made from white polymethyl methacrylate with a light transparency more than 70%. Optical system creates Lambert diffuse reflection. No frame diffuser is equipped with specially formed latches that match the aluminum profile. Luminary is resistant to solids, dust, and humidity penetration – IP20.

2249 x 92 x 86

Product information	Category	Category Surface mounted luminaires	
	Family	ONLINE LED LINE	
	Name	ONLINE LED 10400	PLX E 24 840 LINE-EP / L-2400
	Index	1 <mark>9.3091.0042.24</mark>	
Light and electrical data	Light source	e	LED
	Luminous fl	lux LED [lm]	10468
	LED power	[W]	53,2
	Luminaire lu	umin <mark>ous flux [lm]</mark>	8259
	Power of lu	minaire [W]	56,3
	Luminaire's	light efficiency [lm/W]	146,7
	Color of the	e light [K]	4000
	CRI		>80
	SDCM (LED	D sources)	3
	Beam angle	e [°]	(C0-C180) / (C90-C270) - 93,8° / 96,6°
	Protection a	against electric shock	I
	Protection of	legree	IP20
	Voltage		220240 V, 5060 Hz
	Lifetime of I	LED sources [h]	100000 (1) / 147000 (2)
	Lx/By		L80/B10 (1) / L70/B50 (2)
	Operating t	emperature range [°C]	5 ÷ 30
	Driver		standard on/off (E)
	Power facto	or cos φ	>0,95
	Circuit load	capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)
Mechanical data	Assembly		ctly mounted to ceiling construction or face mounted on slings
A B	Material	alur	ninum
	Color	ano	dised aluminum
	Diffuser	PLX	(PMMA opal)
	Impact resis	stant IK04	1

Dimensions [mm]


A graph of light



Accessories

Index 6E1-500KWAN1P-3

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT




Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023