

## Product: ONLINE LED 2600 PLX E 34 840 LINE-EP / L-567MM Index: 19.3091.0008.34



## Description


Luminary to be mounted on suspensions , or directly on solid ceiling construction. The suspended version is equipped with 1500 mm long suspension system that includes smooth regulation of the suspension length. Its body made from anodized aluminum profile. Luminary is equipped with highly efficient LED sources. Its diffuser is made from white polymethyl methacrylate with a light transparency more than 70%. Optical system creates Lambert diffuse reflection. No frame diffuser is equipped with specially formed latches that match the aluminum profile. Luminary is resistant to solids, dust, and humidity penetration – IP20.

Product information	Category	Surface mounted lu	urface mounted luminaires	
	Family	ONLINE LED LINE		
	Name	ONLINE LED 2600 P	LX E 34 840 LINE-EP / L-567MM	
	Index	19.3091.0008.34		
Light and electrical data	Light source	æ	LED	
	Luminous f	flux LED [lm]	2617	
	LED power	· [W]	13,3	
	Luminaire	luminous flux [lm]	2065	
	Power of Iu	iminaire [W]	14,4	
	Luminaire's	s light efficiency [lm/W]	143,4	
	Color of the	e light [K]	4000	
	CRI		>80	
	SDCM (LE	D sources)	3	
	Beam angl	e [°]	(C0-C180) / (C90-C270) - 93,8° / 96,6°	
	Protection	against electric shock	I	
	Protection	degree	IP20	
	Voltage		220240 V, 5060 Hz	
	Lifetime of	LED sources [h]	100000 (1) / 147000 (2)	
	Lx/By		L80/B10 (1) / L70/B50 (2)	
	Operating	temperature range [°C]	5 ÷ 30	
	Driver		standard on/off (E)	
	Power factor	or cos φ	>0,95	
	Circuit load	I capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)	
Mechanical data	Assembly		ctly mounted to ceiling construction or ace mounted on slings	
AB	Material	alun	ninum	
	Color	RAL	9016 (white)	
	Diffuser	PLX	(PMMA opal)	
	Impact res	istant IK04	L	

Dimensions [mm]

567 x 92 x 86


# A graph of light



## Accessories

## Index 19.3272.0301.34

Name SUSPENSION NEW TYPE-A 34 LENGHT 1,5M WIRE 3X 1-POINT



### Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT




### Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



### Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



### Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023