

Product: PLAFOND ROUND LED 1300 PC E MWS IP54 840 EDRE12/WS/4000**Index:** 19.3092.0002.34

Description

Surface mounted or wall luminaire equipped in highly efficient LED panels. Luminaire body and diffuser made from IK10 impact resistant material. The product is equipped with a microwave motion sensor.

Product information



Category	Surface mounted luminaires
Family	PLAFOND ROUND LED
Name	PLAFOND ROUND LED 1300 PC E MWS IP54 840 EDRE12/WS/4000
Index	19.3092.0002.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	1600
LED power [W]	12
Luminaire luminous flux [lm]	1065
Power of luminaire [W]	14
Luminaire's light efficiency [lm/W]	76,1
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 117,8° / 117,8°
Protection against electric shock	II
Protection degree	IP54
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	54000
Lx/By	L90
Operating temperature range [°C]	0 ÷ 40
Driver	standard on/off (E)

Mechanical data



Assembly	surface mounted on ceiling or on wall
Material	polycarbonate
Color	white
Diffuser	PC (opalescent polycarbonate)
Impact resistant	IK10
Dimensions [mm]	Ø280 x 63

A graph of light

