

Product: RUBIN LOOK LED 8800 PLX E IP44 34 830 / 600X600

Index: 19.3096.0042.34



Description

Surface mounted luminaire for LED sources. Luminaire body made from steel sheet, powder coated. Luminaire recommended for: wards and hospital bathrooms. Dust, and humidity penetration: IP44.

Product information

Category	Surface mounted luminaires
Family	RUBIN LOOK LED IP44
Name	RUBIN LOOK LED 8800 PLX E IP44 34 830 / 600X600
Index	19.3096.0042.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	8811
LED power [W]	46,8
Luminaire luminous flux [lm]	6270
Power of luminaire [W]	49,1
Luminaire's light efficiency [lm/W]	127,7
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 108,2° / 107,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP44
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	15 (B10), 25 (B16), 24 (C10), 38 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	6,84
Dimensions [mm]	620 x 625 x 61

A graph of light

