

**Product:** RUBIN LOOK LED SMOOTH 7500 PLX EDD IP44 34 830 / 1200X300

**Index:** 19.3097.0021.34



## Description

Surface mounted luminaire equipped in highly efficient LED sources. Luminaire body made from steel sheet, powder coated.

## Product information


|          |   |
|----------|---|
| Category | Surface mounted luminaires                                |
| Family   | RUBIN LOOK LED SMOOTH                                     |
| Name     | RUBIN LOOK LED SMOOTH 7500 PLX EDD IP44 34 830 / 1200X300 |
| Index    | 19.3097.0021.34   |



## Light and electrical data

|                                     |  |
|-------------------------------------|--|
| Light source                        | LED                                      |
| Luminous flux LED [lm]              | 7875                                     |
| LED power [W]                       | 39,8                                     |
| Luminaire luminous flux [lm]        | 5924                                     |
| Power of luminaire [W]              | 42,2                                     |
| Luminaire's light efficiency [lm/W] | 140,4                                    |
| Color of the light [K]              | 3000                                     |
| CRI                                 | >80                                      |
| SDCM (LED sources)                  | 3  |
| Beam angle [°]                      | (C0-C180) / (C90-C270) - 109,6° / 109,6° |
| Protection against electric shock   | I  |
| Protection degree                   | IP44                                     |
| Voltage                             | 220..240 V, 50..60 Hz                    |
| Lifetime of LED sources [h]         | 60000                                    |
| Lx/By                               | L80/B10                                  |
| Operating temperature range [°C]    | 5 ÷ 30                                   |
| Driver                              | DIM DALI (EDD)                           |
| Power factor cos φ                  | >0,95                                    |
| Circuit load capacity               | 8 (B10), 13 (B16), 13 (C10), 21 (C16)    |

## Mechanical data



|                  |                            |
|------------------|----------------------------|
| Assembly         | surface mounted on ceiling |
| Material         | steel sheet                |
| Color            | RAL 9016 (white)           |
| Diffuser         | PLX (PMMA opal)            |
| Impact resistant | IK04                       |
| Dimensions [mm]  | 1140 x 368 x 56            |

## A graph of light

