

## Product: UNIVERSAL LINE E 24 3F IP20 LINE-S / L-1159MM Index: 19.3127.0036.24

	Description White the system is built on the base of aluminium profile of crosswise dimension after assembly 60 mm x 75 mm, LED strips and linear lenses. Standard plates to the ceiling) - suspended line. The construction of the luminary ensures or of the three levels of protection: IP20, IP55 or IP65. IP20 and IP65 versions of the product are dedicated for internal use. Versions IP55 of the luminary are dedicated for external use. In order to achieve the level of protection IP55, luminating part should be directed downwards. It is forbidden to install the uninary on the wall or directed upwards.	
Product information	Category Surface mounted luminaires	
	Family UNIVERSAL LINE LED	
	Name UNIVERSAL LINE E 24 3F IP20 LINE-S / L-1159MM	
	Index 19.3127.0036.24	
	CE	$\textcircled{\mathbb{E}} \bigoplus \textcircled{\mathbb{P}}_{20} \widecheck{\mathbb{K}}_{4} \bigoplus \textcircled{\mathbb{E}}_{\mathbb{N}}$
Light and electrical data	Light source	none
	Luminous flux LED [lm]	N/A
	LED power [W]	N/A
	Luminaire luminous flux [lm]	N/A
	Power of luminaire [W]	N/A
	Luminaire's light efficiency [lm/W]	N/A
	Color of the light [K]	N/A
	Protection against electric shock	I
	Protection degree	IP20
	Voltage	220240 V, 5060 Hz
	Driver	standard on/off (E)
Mechanical data		tly mounted to ceiling construction or ce mounted on slings
	Material alumi	inum
	Color anod	ised aluminum
	Diffuser not a	vailable in 3F version
	Impact resistant IK04	
	Weight [kg] 2,65	
	Dimensions [mm]	

Dimensions [mm]

1159 x 60 x 75







## Accessories







Name SUSPENSION NEW TYPE-A+B 24



Index 6E1-8670-B-1,5-5X

Name SUSPENSION NEW TYPE-F



Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT

