

**Product:** KUBIK CEILING ECO LED 2X GU10 IP54 04**Index:** 19.3148.0002.04

## Description

Architectural luminaire designed for ceiling mounting. The body is made of aluminum. Interchangeable light sources with the popular GU10 socket. The ergonomic shapes of the luminaire allow the use of KUBIK in almost every building. Very easy assembly. Luminaire with IP54 protection rating.

## Product information


|          |                                       |
|----------|---------------------------------------|
| Category | Outdoor luminaires                    |
| Family   | KUBIK CEILING ECO LED                 |
| Name     | KUBIK CEILING ECO LED 2X GU10 IP54 04 |
| Index    | 19.3148.0002.04                       |



## Light and electrical data

|                                     |  |
|-------------------------------------|--|
| Light source                        | RETROFIT GU10 (not included)             |
| Luminous flux LED [lm]              | depending on applied light source        |
| LED power [W]                       | depending on applied light source        |
| Luminaire luminous flux [lm]        | depending on applied light source        |
| Power of luminaire [W]              | depending on applied light source        |
| Luminaire's light efficiency [lm/W] | depending on applied light source        |
| Color of the light [K]              | depending on applied light source        |
| CRI                                 | depending on applied light source        |
| SDCM (LED sources)                  | depending on applied light source        |
| Beam angle [°]                      | (C0-C180) / (C90-C270) - 111,4° / 111,4° |
| Protection against electric shock   | I  |
| Protection degree                   | IP54                                     |
| Voltage                             | 220..240 V, 50..60 Hz                    |
| Lifetime of LED sources [h]         | depending on applied light source        |
| Lx/By                               | depending on applied light source        |
| Driver                              | none                                     |

## Mechanical data



|                  |                               |
|------------------|-------------------------------|
| Assembly         | surface mounted on ceiling    |
| Material         | aluminum                      |
| Color            | RAL 9005 (black)              |
| Diffuser         | PC (opalescent polycarbonate) |
| Impact resistant | IK04                          |
| Weight [kg]      | 1,17                          |
| Dimensions [mm]  | 200 x 120 x 120               |

## A graph of light

