


Product: KUBIK POLE 600 3/3/3/3 LED 1,7W E IP65 22 3000K Index: 19.3160.0053.22




Description

Outdoor luminary for assembling on a hardened surface (concrete, sett, or basement) equipped with the highly effective power saving LED sources of the newest generation. It is dedicated to illuminate pedestrian router such as park alleys, parking spaces communication routes, estate entrances. Luminary body coated with facade paint dedicated for outdoor usage, light sources placed in upper part of the luminary with the asymmetric lens providing illumination of the area. IP65 hermetic luminary, IK09 strike resistant. Luminary available in variety of colors from RAL color palette upon the clients request. Luminary height: 300, 600, 900, 3000 and 4000 mm.

Product information	Category Outdoor luminaires	
	Family KUBIK POLE	LED
	Name KUBIK POLE	600 3/3/3/3 LED 1,7W E IP65 22 3000K
	Index 19.3160.0053	
Light and electrical data	Light source	LED
	Luminous flux LED [lm]	1488
	LED power [W]	20
	Luminaire luminous flux [lm	1] 1211
	Power of luminaire [W]	23
	Luminaire's light efficiency	[lm/W] 52,7
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	5
	Beam angle [°]	asymmetric light distribution
	Protection against electric s	shock I
	Protection degree	IP65
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	50000
	Lx/By	L70/B50
	Operating temperature ran	ge [°C] -25 ÷ 30
	Driver	standard on/off (E)
	Power factor $\cos \phi$	>0,5
	Circuit load capacity	20 (B10), 30 (B16), 33 (C10), 53 (C16)
Mechanical data	Assembly	for the ground
	Material	aluminum
	Color	RAL 9007 (dark gray, metallic, fine structure)
	Diffuser	transparent polycarbonate
	Impact resistant	IK09
	Weight [kg]	5,61
	Dimensions [mm]	150 x 150 x 600



A graph of light



Accessories

Index 2TJ5782-3 Name 5782-3 Foundations RAL9007



Index 2TJ5782-4 Name 5782-4 Foundations

