

## Product: KUBIK POLE T 10000 STREET-M E IP65 04 757 / 4000/1700MM Index: 19.3164.0002.04



## Description


Outdoor luminary for assembling on a hardened surface (concrete, sett, or basement) equipped with the highly effective power saving LED sources of the newest generation. The system is designed and optimized for lighting streets, parks, gardens. Corrosion resistant extruded aluminum aesthetic housing and special pole arrangement. Easy installation, tool less, easy maintenance. Optimal performance with a glare-free, full cutoff, uniform lighting distribution. Note: Luminaires up to 6 m high can be safely used in the first and third wind zones (according to PN-EN 1991-1-4) and in the third and fourth terrain categories (according to PN-EN 40-3-1: 2004). Il wind zone and other terrain categories require an individual assessment of the maximum binding height. The type and dimensions of the foundation each time depend on the foundation conditions. The final selection of the foundation, in accordance with the Building Law, is the responsibility of the designer of the object.

Product information	Category Outdoor luminaires	
	Family KUBIK POLE T LED	
	Name KUBIK POLE T 10000 STREET-M E IP65 04 757 / 4000/1700	ОММ
	Index 19.3164.0002.04	
	$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \end{array}{\end{array}}$	
ight and electrical data	Light source LED	
	Luminous flux LED [lm] 9933	
	LED power [W] 67	
	Luminaire luminous flux [lm] 9400	
	Power of luminaire [W] 75	
	Luminaire's light efficiency [lm/W] 125,3	
	Color of the light [K] 5700	
	CRI >70	
	SDCM (LED sources) 5	
	Beam angle [°] street light distribution	
	Protection against electric shock	
	Protection degree IP65	
	Voltage 220240 V, 5060 Hz	
	Lifetime of LED sources [h] 50000	
	Lx/By L70/B10	
	Operating temperature range [°C] -25 ÷ 30	
	Driver standard on/off (E)	
	Power factor $\cos \varphi$ >0,95	
	Circuit load capacity 6 (B10), 10 (B16), 10 (C10), 17 (C	C16)
lechanical data	Assembly for the ground	
	Material aluminum	
	Color RAL 9005 (black)	
	Diffuser transparent polycarbonate	
	Impact resistant IK04	
	Dimensions [mm] 1700 x 260 x 4000	

\_\_\_\_\_α



## A graph of light



## Accessories

Index 17ROFU311151 Name B-51 Foundations



Index 50RO4008 Name ROSA set of galvanized nuts for B-60



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023