

Product: KUBIK POLE T 20000LM STREET-M E IP65 04 757 / 3000/1700MM

Index: 19.3164.0007.04



Description

Outdoor luminary for assembling on a hardened surface (concrete, sett, or basement) equipped with the highly effective power saving LED sources of the newest generation. The system is designed and optimized for lighting streets, parks, gardens. Corrosion resistant extruded aluminum aesthetic housing and special pole arrangement. Easy installation, tool less, easy maintenance. Optimal performance with a glare-free, full cutoff, uniform lighting distribution. Note: Luminaires up to 6 m high can be safely used in the first and third wind zones (according to PN-EN 1991-1-4) and in the third and fourth terrain categories (according to PN-EN 40-3-1: 2004). Il wind zone and other terrain categories require an individual assessment of the maximum binding height. The type and dimensions of the foundation each time depend on the foundation conditions. The final selection of the foundation, in accordance with the Building Law, is the responsibility of the designer of the object.

Product information

Category Outdoor luminaires

Family KUBIK POLE T LED

Name KUBIK POLE T 20000LM STREET-M E IP65 04 757 / 3000/1700MM

Index 19.3164.0007.04














Light and electrical data

LED
19867
134
18800
150
125,3
5700
>70
5
street light distribution
I
IP65
220240 V, 5060 Hz
50000
L70/B10
-25 ÷ 30
standard on/off (E)
>0,95
5 (B10), 8 (B16), 8 (C10), 13 (C16)


Mechanical data



Assembly	for the ground
Material	aluminum
Color	RAL 9005 (black)
Diffuser	transparent polycarbonate
Impact resistant	IK04
Weight [kg]	30
Dimensions [mm]	1700 x 260 x 3000



A graph of light



Accessories

Index 17R0FU311151

Name B-51 Foundations



Index 50RO4008

Name ROSA set of galvanized nuts for B-60

