

## Product: AGAT LED S DECO SMOOTH 5400 MICRO-PRM E 840 / 600X600 Index: 19.4006.1121.34



## Description

Housing luminaire for suspended module ceilings. Housing made of steel sheet powder coated in white. Characteristic feature of Agat LED Deco Smooth is ,inserted' diffuser, which after the luminaire is mounted is above the level of ceiling. This solution gives very interesting, original and decorative effect. The luminaire is available with milky colour diffuser PLX or micro-prismatic and is equipped with highly efficient LED light source. Luminous flux of LED light source is 5400 lm. The colour temperature 3000 K or 4000 K. The luminaire is recommended to illuminate public utility facilities.


Product information	Index 19.4006.1121.34	
Light and electrical data	Light source Luminous flux LED [lm] LED power [W] Luminaire luminous flux [lm]	LED 5607 30,6 4832
	Power of luminaire [W] Luminaire's light efficiency [Im/V Color of the light [K] CRI	33,2 //] 145,5 4000 >80
	SDCM (LED sources) Beam angle [°]	3 (C0-C180) / (C90-C270) - 87,4° / 89,2°
	Protection against electric shock Protection degree	k I IP20
	Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 54000
	Lx/By Operating temperature range [°	L80/B10 <sup>2</sup> C] 5 ÷ 30
	Driver	standard on/off (E)
	Power factor cos φ Circuit load capacity	>0,95 22 (B10), 34 (B16), 33 (C10), 54 (C16)
Mechanical data		nounted in module ceilings, as well as lasterboard ceilings
	Material si	teel sheet
В	Color w	hite
	Diffuser M	licro-PRM (micro-prismatic diffuser PMMA)
<u></u> н		<04
A		,52
	Dimensions [mm] 59	95 x 595 x 120

Mounting hole [mm]

580 x 580



## A graph of light



## Accessories

Index 2M-X414LKP90

Name Mounting clips set for plasterboard ceiling



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023