

Product: ARTSHAPE OVAL LED MEDIUM FULL-S SUSPENDED 9900 PLX E 04 840 / L-1315MM, S-1,5M Index: 19.4011.1121.04



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information			
		Category Architectural luminaires	
		Family ARTSHAPE OVAL LED FULL-S	
		Name ARTSHAPE OVAL LED MEDIUM FULL-S SUSPENDED 9900 PL 04 840 / L-1315MM, S-1,5M	XE
		Index 19.4011.1121.04	
		$\overbrace{LED} \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus \bigoplus_{hdoor} \bigoplus_{hdoor}$	Ø
Light and electrical data		Light source LED	
		Luminous flux LED [Im] 11732	
		LED power [W] 68,9	
		Luminaire luminous flux [lm] 6218	
		Power of luminaire [W] 77,2	
		Luminaire's light efficiency [lm/W] 80,5	
		Color of the light [K] 4000	
		CRI >80	
		SDCM (LED sources) 3	
		Photobiological risk class (IEC/EN 62471) RG0	
		Protection against electric shock	
		Protection degree IP40	
		Voltage 220240 V, 5060 Hz	
		Lifetime of LED sources [h] 100000 (1) / 80000 (2)	
		Lx/By L70/B10 (1) / L80/B10 (2)	
		Operating temperature range [°C] 5 ÷ 30	
		Driver standard on/off (E)	
		Power factor $\cos \phi$ 0,95	
		Circuit load capacity 7 (B10), 12 (B16), 12 (C10), 14 (C16
Mechanical data		Assembly surface mounted on slings	
	Ĭ I	Material aluminum	
	1500	Color RAL 9005 (black)	
	17	Diffuser PLX (PMMA opal)	
		Impact resistant IK04	
	<u> </u>	Weight [kg] 4,95	
r1		Dimensions [mm] 1315 x 230 x 85	

Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023