

Product: ARTSHAPE OVAL LED MEDIUM FULL-S SUSPENDED 9900 PLX EDD 21 840 / L-1315MM, S-1,5M Index: 19.4011.1123.21



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information		Category Architectural luminaires		
		Family ARTSHAPE OVAL LED FU	LL-S	
		Name ARTSHAPE OVAL LED MEDIUM FULL-S SUSPENDED 9900 PLX EDD 21 840 / L-1315MM, S-1,5M		
		Index 19.4011.1123.21		
			P	
Light and electrical data		Light source	LED	
		Luminous flux LED [lm]	11732	
		LED power [W]	68,9	
		Luminaire luminous flux [lm]	6218	
		Power of luminaire [W]	77,2	
		Luminaire's light efficiency [lm/W]	80,5	
		Color of the light [K]	4000	
		CRI	>80	
		SDCM (LED sources)	3	
		Photobiological risk class (IEC/EN 624	71) RG0	
		Protection against electric shock	I	
		Protection degree	IP40	
		Voltage	220240 V, 5060 Hz	
		Lifetime of LED sources [h]	100000 (1) / 80000 (2)	
		Lx/By	L70/B10 (1) / L80/B10 (2)	
		Operating temperature range [°C]	5 ÷ 30	
		Driver	DIM DALI (EDD)	
		Power factor $\cos \phi$	0,95	
		Circuit load capacity	7 (B10), 11 (B16), 11 (C10), 12 (C16)	
Mechanical data		Assembly surfa	ace mounted on slings	
	T	Material alum	inum	
	200	Color RAL	RAL 9006 (gray, metallic, fine structure)	
	12	Diffuser PLX	(PMMA opal)	
		Impact resistant IK04		
	<u> </u>	Weight [kg] 4,95		
		Dimensions [mm] 1315	x 230 x 85	

Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023