

Product: ARTSHAPE ROUND LED MEDIUM EDGE SUSPENDED 4500 PLX E 34 830 / S-1,5M Index: 19.4012.2211.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

RG0

IP40

60000

0 ÷ 30

>0,95

L80/B10

220..240 V, 50..60 Hz

standard on/off (E)

12 (B10), 19 (B16), 20 (C10), 32 (C16)

I

Product information		Category Architectural luminaires		
		Family ARTSHAPE ROUND LED		
		Name	ART <mark>SHAPE R</mark> OUND LED 34 830 / S-1,5M	MEDIUM EDGE SUSPENDED 4500 PLX E
		Index	19.4012.2211.34	
				$\textcircled{E} \textcircled{P}_{40} \H{K}_{4} \textcircled{E}_{1000} $
Light and electrical data		Light sou	irce	LED
		Luminou	s flux LED [lm]	4262
		LED pow	ver [W]	32
		Luminair	e luminous flux [lm]	2235
		Power of	f luminaire [W]	35
		Luminair	e's light efficiency [lm/W]	63,9
		Color of	the light [K]	3000
		CRI		>80
		SDCM (L	ED sources)	3
		Beam an	ngle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°

Photobiological risk class (IEC/EN

Protection against electric shock

Operating temperature range [°C]

Lifetime of LED sources [h]

62471)

Voltage

Lx/By


Driver

Protection degree

Power factor cos φ Circuit load capacity




Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	Ø900 x 85

A graph of light



Accessories

Index 6E1-500OKW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

