


Product: ARTSHAPE ROUND LED MEDIUM EDGE SUSPENDED 9000 PLX EDD 34 830 / S-1,5M Index: 19.4012.2413.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

220..240 V, 50..60 Hz

DIM DALI (EDD)

14 (B10), 23 (B16), 22 (C10), 35 (C16)

60000

0 ÷ 30

>0,95

L80/B10

Product information	Category Architectural lun	ninaires
	Family ARTSHAPE ROU	ND LED
	Name ARTSHAPE ROU EDD 34 830 / S-1	ND LED MEDIUM EDGE SUSPENDED 9000 PLX ,5M
	Index 19.4012.2413.34	
	CE	LED E LED LA IN CONTRACT
Light and electrical data	Light source	LED
	Luminous flux LED [lm]	8521
	LED power [W]	64
	Luminaire luminous flux [lm]	4468
	Power of luminaire [W]	70
	Luminaire's light efficiency [l	m/W] 63,8
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
	Photobiological risk class (IE 62471)	EC/EN RG0
	Protection against electric sh	nock I
	Protection degree	IP40

Voltage

Lx/By

Driver


Lifetime of LED sources [h]

Power factor cos φ Circuit load capacity

Operating temperature range [°C]




Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	Ø900 x 85

A graph of light



Accessories

Index 6E1-500OKW1P-5

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

