


9 (B10), 15 (B16), 15 (C10), 24 (C16)

Product: ARTSHAPE SIX LED SMALL EDGE SUSPENDED 9000 PLX E 34 840 / S-1,5M Index: 19.4015.1421.34




Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information		Category Architectural luminaires		
		Family ARTSHAPE SIX LED		
		Name	Name ARTSHAPE SIX LED SMALL EDGE SUSPENDED 9000 PLX E / S-1,5M	
		Index	19.4015.1421.34	
				E
Light and electrical data		Light sou	urce	LED
		Luminou	is flux LED [lm]	8910
		LED pov	ver [W]	64
		Luminair	re luminous flux [lm]	4672
		Power of	f luminaire [W]	70
		Luminai	re's light efficiency [lm/W]	66,7
		Color of	the light [K]	4000
		CRI		>80
		SDCM (I	LED sources)	3
		Beam ar	ngle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
		Photobic 62471)	ological risk class (IEC/EN	RG0
		Protectio	on against electric shock	I
		Protectio	on degree	IP40
		Voltage		220240 V, 5060 Hz
		Lifetime	of LED sources [h]	60000
		Lx/By		L80/B10
		Operatin	ng temperature range [°C]	0 ÷ 30
		Driver		standard on/off (E)
		Power fa	actor cos φ	>0,95


Circuit load capacity

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	4,6
Dimensions [mm]	650 x 592 x 85

A graph of light



Accessories

Index 6E1-500OKW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

