

Product: ARTSHAPE SIX LED LARGE FULL UP&DOWN 5000/21000 PLX E 34 840 / S-1,5M

Index: 19.4016.6621.34



## **Description**

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

### **Product information**

Category Architectural luminaires		
Family	ARTSHAPE SIX LED	
Name	ARTSHAPE SIX LED LARGE FULL UP&DOWN 5000/21000 PLX E 34 840 / S-1,5M	
Index	19.4016.6621.34	















## Light and electrical data

Light source	LED
Luminous flux LED [lm]	5320/21782
LED power [W]	40/156
Luminaire luminous flux [lm]	20738
Power of luminaire [W]	218
Luminaire's light efficiency [lm/W]	95,1
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	4
Beam angle [°]	(C0-C180) / (C90-C270) - 111,2° / 114,2°
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	35000
Lx/By	L80/B10
Operating temperature range [°C]	0 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	2 (B10), 3 (B16), 4 (C10), 6 (C16)

#### Mechanical data






Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	1170 x 1043 x 85



# A graph of light



## **Accessories**

Index 6E1-5000KW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

