


Product: ARTSHAPE SQ LED SMALL EDGE SUSPENDED 4000 PLX E 34 840 / S-1,5M Index: 19.4017.1721.34




Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information	Category Architectural luminaires		
	Family Name	ARTSHAPE SQ LED ARTSHAPE SQ LED SMALL EDGE SUSPENDED 4000 PLX E	34 840
	Name	/ S-1,5M	54 040
	Index	19.4017.1721.34	
		$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \textcircled{} \end{array}{} \textcircled{} \end{array}{\end{array}}$	
Light and electrical data	Light sou	burce LED	
	Luminou	us flux LED [lm] 3960	
	LED pow	wer [W] 28	
	Luminair	ire luminous flux [lm] 2077	


	Luminous flux LED [lm]	3960
	LED power [W]	28
	Luminaire luminous flux [lm]	2077
	Power of luminaire [W]	32
	Luminaire's light efficiency [lm/W]	64,9
	Color of the light [K]	4000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
	Photobiological risk class (IEC/EN 62471)	RG0
	Protection against electric shock	I
	Protection degree	IP40
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	60000
	Lx/By	L80/B10
	Operating temperature range [°C]	0 ÷ 30
	Driver	standard on/off (E)
	Power factor cos φ	>0,95
	Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	5,88
Dimensions [mm]	660 x 660 x 85

A graph of light



Accessories

Index 6E1-500OKW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

