

Product: ARTSHAPE SQ LED LARGE EDGE SUSPENDED TW 10000 PLX EDD 34 827-865 / S-1,5M

Index: 19.4017.3953.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. LED modules adjusted to regulate the color temperature of light in the range from 2700 K to 6500 K.

Product information

Category Architectural luminaires

Family ARTSHAPE SQ LED

Name ARTSHAPE SQ LED LARGE EDGE SUSPENDED TW 10000 PLX EDD 34 827-865 / S-1,5M

Index 19.4017.3953.34
















Light and electrical data

| Light source | LED |
|-------------------------------------|--|
| Luminous flux LED [lm] | 10440 |
| LED power [W] | 91 |
| Luminaire luminous flux [lm] | 5475 |
| Power of luminaire [W] | 100 |
| Luminaire's light efficiency [lm/W] | 54,8 |
| Color of the light [K] | 2700 ÷ 6500 |
| CRI | >80 |
| SDCM (LED sources) | 4 |
| Beam angle [°] | (C0-C180) / (C90-C270) - 113,4° / 111,8° |
| Protection against electric shock | I |
| Protection degree | IP40 |
| Voltage | 220240 V, 5060 Hz |
| Lifetime of LED sources [h] | 60000 |
| Lx/By | L80/B10 |
| Operating temperature range [°C] | 0 ÷ 30 |
| Driver | DIM DALI (EDD) |
| Power factor cos φ | >0,95 |
| Circuit load capacity | 8 (B10), 14 (B16), 15(C10), 25 (C16) |


Mechanical data



| Assembly | surface mounted on slings |
|------------------|---------------------------|
| Material | aluminum |
| Color | RAL 9016 (white) |
| Diffuser | PLX (PMMA opal) |
| Impact resistant | IK04 |
| Dimensions [mm] | 1200 x 1200 x 85 |



A graph of light



Accessories

Index 6E1-5000KW1P-5

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

