


Product: ARTSHAPE SQ LED SMALL FULL SUSPENDED 4500 PLX E 34 840 / S-1,5M Index: 19.4019.1221.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

220..240 V, 50..60 Hz

standard on/off (E)

19 (B10), 30 (B16), 31 (C10), 50 (C16)

60000

0 ÷ 30

>0,95

L80/B10

Product information		Category Architectural luminaires						
		Family	Family ARTSHAPE SQ LED					
		Name ARTSHAPE SQ LED SMALL FULL SUSPENDED 4500 PLX E 34						
		Index	19.4019.1221.34					
							Indoor	
Light and electrical data		Light sou	urce		LED			
J. J		Luminous flux LED [lm]			4455			
		LED power [W]			32			
			e luminous flux [lm]		3276			
		Power of	f luminaire [W]		35			
		Luminair	e's light efficiency [l	m/W]	93,6			
		Color of the light [K]			4000			
		CRI SDCM (LED sources)			>80 3			
								Beam angle [°]
		Photobiological risk class (IEC/EN Re 62471)			RG0			
				Protectio	on against electric sł	nock	I	
		Protectio	on degree		IP20			

Voltage

Lx/By


Driver

Lifetime of LED sources [h]

Power factor cos φ Circuit load capacity


Operating temperature range [°C]

Mechanical data



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	6,45
Dimensions [mm]	660 x 660 x 85

A graph of light



Accessories

Index 6E1-500OKW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

