


# Product: ARTSHAPE SQ LED SMALL FULL SUSPENDED 12000 PLX E 34 840 / S-1,5M Index: 19.4019.1621.34




#### Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information	Category Architectural luminaires		
	Family	ARTSHAPE SQ LED	
	Name	ARTSHAPE SQ LED SM 840 / S-1,5M	ALL FULL SUSPENDED 12000 PLX E 34
	Index	19.4019.1621.34	
		CE	
Light and electrical data	Light sou	urce	
Light and electrical data	Ū	urce us flux LED [Im]	
Light and electrical data	Ū	is flux LED [lm]	LED
Light and electrical data	Luminou LED pow	is flux LED [lm]	LED 11358
Light and electrical data	Luminou LED pow Luminair	is flux LED [lm] ver [W]	LED 11358 85
Light and electrical data	Luminou LED pow Luminair Power of	us flux LED [lm] ver [W] re luminous flux [lm]	LED 11358 85 8353


Luminaire luminous flux [lm]	8353
Power of luminaire [W]	93
Luminaire's light efficiency [lm/W]	89,8
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 111,2° / 114,2°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP20
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	0 ÷ 30
Driver	standard on/off (E)
Power factor $\cos \phi$	>0,95
Circuit load capacity	9 (B10), 15 (B16), 15 (C10), 24 (C16)

## **Mechanical data**



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	7,69
Dimensions [mm]	660 x 660 x 85

## A graph of light



### Accessories

Index 6E1-500OKW1P-3

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

