

# Product: ARTSHAPE THREE LED SMALL EDGE SUSPENDED 3000 PLX EDD 34 840 / S-1,5M Index: 19.4020.1123.34




#### Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on slings. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres.

Product information		Category Architectural luminaires	
		Family ARTSHAPE THREE LED	
		Name ARTSHAPE THREE LED SMALL EDGE SUSPENDED 3000 PLX E 34 840 / S-1,5M	EDD
		Index 19.4020.1123.34	
		$\overbrace{LED} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \textcircled{} \end{array}{} \end{array}{\end{array}}$	Ì
Light and electrical data		Light source LED	
-		Luminous flux LED [lm] 2970	
		LED power [W] 21	
		Luminaire luminous flux [lm] 1557	
		Power of luminaire [W] 25	
		Luminaire's light efficiency [lm/W] 62,3	
		Color of the light [K] 4000	


LED power [W]	21
Luminaire luminous flux [lm]	1557
Power of luminaire [W]	25
Luminaire's light efficiency [lm/W]	62,3
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	60000
Lx/By	L80/B10
Operating temperature range [°C]	0 ÷ 30
Driver	DIM DALI (EDD)
Power factor $\cos \phi$	>0,95
Circuit load capacity	12 (B10), 20 (B16), 20 (C10), 32 (C16)

#### **Mechanical data**



Assembly	surface mounted on slings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	3,98
Dimensions [mm]	630 x 575 x 85

## A graph of light



### Accessories

Index 6E1-500OKW1P-5

Name SUSPENSION NEW TYPE-J 34 LENGHT 1,5M WIRE 5X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT

