

Product: AGAT CLEAN LED 13200 MICRO-PRM E IP65 830 / 1200X600**Index:** 19.4028.1311.34

Description

Luminaire designed to module and gypsum and cardboard suspended ceilings, equipped with the highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Optical systems and diffusers mounted in an aluminum frame. Luminaire recommended for: emergency departments, intensive care units, and treatment rooms. *Selected luminaire variants are available with ENEC certificate.

Product information


Category	Clean luminaires - recessed
Family	AGAT CLEAN LED
Name	AGAT CLEAN LED 13200 MICRO-PRM E IP65 830 / 1200X600
Index	19.4028.1311.34



Light and electrical data


Light source	LED
Luminous flux LED [lm]	13217
LED power [W]	70,2
Luminaire luminous flux [lm]	9814
Power of luminaire [W]	71,6
Luminaire's light efficiency [lm/W]	137,1
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	8 (B10), 12 (B16), 13(C10), 21 (C16)

Mechanical data



Assembly	mounted in module ceilings, as well as plasterboard ceilings
Material	steel sheet
Color	white
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1196 x 596 x 76
Mounting hole [mm]	1180 x 580

A graph of light



Accessories

Index	2M-X414LKPIPT5
Name	Mounting clips set for plasterboard ceiling

