

Product: ARTSHAPE LINE WALL L-320 UP&DOWN 650/650 PLX E 34 830 Index: 19.4049.1111.34



Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on the wall. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

(C16)

Product information	Category Architectural luminaires Family ARTSHAPE LINE WALL Name ARTSHAPE LINE WALL L-320 UP&DOWN 650/0	amily ARTSHAPE LINE WALL	
	Index 19.4049.1111.34 $\overbrace{\text{LED}}$ $\overbrace{\text{ED}}$ $\overbrace{\text{ED}}$ $\overbrace{\text{ED}}$ $\overbrace{\text{LED}}$		
Light and electrical data	Light source LED		
5	Luminous flux LED [lm] 1349		
	LED power [W] 8		
	Luminaire luminous flux [lm] 707		
	Power of luminaire [W] 9		
	Luminaire's light efficiency [lm/W] 78,6		
	Color of the light [K] 3000		
	CRI >80		
	SDCM (LED sources) 3		
	Beam angle [°] (C0-C180) / (C90- 111,8°	C270) - 113,4° /	
	Photobiological risk class (IEC/EN RG0 62471)		
	Protection against electric shock		
	Protection degree IP40		
	Voltage 220240 V, 5060	Hz	
	Lifetime of LED sources [h] 60000		
	Lx/By L80/B10		
	Operating temperature range [°C] 0 ÷ 30		
	Driver standard on/off (I	Ξ)	
	Power factor $\cos \phi$ >0,95		
	Circuit load capacity 40 (B10), 60 (B16)	, 64 (C10), 102	



Product card

Mechanical data

. A .	B

Assembly	mounted on wall
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1,2
Dimensions [mm]	320 x 110 x 85

A graph of light

