

## Product: ARTSHAPE LINE WALL L-600 UP&DOWN 1300/1300 PLX E 25 840 Index: 19.4049.2221.25



## Description

Modernistic architectural luminary in shapes of popular geometrical figures and fashionable design of simple form. The luminary is adjusted to be mounted on the wall. It is equipped with highly efficient LED light sources. Various options of luminous flux and colour temperature are available. The sides of the shade are made of thin-walled aluminium profile. In combination with a possibility of painting according to RAL palete, the luminaries allow to achieve a unique arrangement of various premises. Perfectly even surface-emitting is made of material which has very good light transmittance factor and has good diffusion parameters. This luminary is dedicated to room of high stylistic requirements. It is perfect for hotel atrium, office receptions, architectural studios, conference rooms or halls and corridors in exclusive buildings as well as for theatres or modern shops in shopping centres. Direct-indirect light distribution.

Product information		Category Architectural luminaires		
		Family ARTSHAPE LINE WALL		
		Name ARTSHAPE LINE WALL L	-600 UP&DOWN 1300/1300 PLX E 25 840	
		Index 19.4049.2221.25		
Light and electrical data	cal data	Light source	LED	
		Luminous flux LED [lm]	2840	
		LED power [W]	15	
		Luminaire luminous flux [lm]	1489	
		Power of luminaire [W]	17	
		Luminaire's light efficiency [lm/W]	87,6	
		Color of the light [K]	4000	
		CRI	>80	
		SDCM (LED sources)	3	
		Beam angle [°]	(C0-C180) / (C90-C270) - 113,4° / 111,8°	
		Photobiological risk class (IEC/EN 62471)	RG0	
		Protection against electric shock	I	
		Protection degree	IP40	
		Voltage	220240 V, 5060 Hz	
		Lifetime of LED sources [h]	60000	
		Lx/By	L80/B10	
		Operating temperature range [°C]	0 ÷ 30	
		Driver	standard on/off (E)	
		Power factor $\cos \phi$	>0,95	
		Circuit load capacity	12 (B10), 19 (B16), 20 (C10), 32 (C16)	



## **Mechanical data**

ļ	Ă	<u> </u>

Assembly	mounted on wall
Material	aluminum
Color	RAL 7016 (anthracite, metallic, fine structure)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Dimensions [mm]	600 x 110 x 85

## A graph of light



