

Product: AGAT CLEAN NO FRAME LED 7800 SHM E IP65 840 / 1200X600

Index: 19.4054.2121.34



Description

Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. Luminary recommended for: operating and treatment rooms, as well as intensive care units.

Product information

Category	Clean luminaires - recessed
Family	AGAT CLEAN NO FRAME LED
Name	AGAT CLEAN NO FRAME LED 7800 SHM E IP65 840 / 1200X600
Index	19.4054.2121.34















Light and electrical data

Light source	LED
Luminous flux LED [lm]	7851
LED power [W]	39,9
Luminaire luminous flux [lm]	6319
Power of luminaire [W]	43,1
Luminaire's light efficiency [lm/W]	146,6
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
Protection against electric shock	I
Protection degree	IP65
Voltage	220240 V, 5060 Hz
	22011240 V, 001100 112
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lifetime of LED sources [h] Lx/By	•
	100000 (1) / 147000 (2)
Lx/By	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2)
Lx/By Operating temperature range [°C]	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) 5 ÷ 30


Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	white
Diffuser	SHM (hardened mat glass)
Impact resistant	IK08
Dimensions [mm]	1196 x 596 x 67
Mounting hole [mm]	1180 x 580



A graph of light



Accessories

Index 6BZBO60980

Name Handle for pane opening

