

Product: AGAT CLEAN NO FRAME LED 10400 SHM E IP65 830 / 1200X600 Index: 19.4054.2211.34



Description

Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. Luminary recommended for: operating and treatment rooms, as well as intensive care units.


Product information	Category Clean luminaires - rec Family AGAT CLEAN NO FRA Name AGAT CLEAN NO FRA Index 19.4054.2211.34	
Light and electrical data	Light source	LED
	Luminous flux LED [Im]	10102
	LED power [W]	53,2
	Luminaire luminous flux [lm]	8131
	Power of luminaire [W]	56,3
	Luminaire's light efficiency [lm/W]	144,4
	Color of the light [K]	3000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 109,6° / 109,6°
	Protection against electric shock	I
	Protection degree	IP65
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources [h]	100000 (1) / 147000 (2)
	Lx/By	L80/B10 (1) / L70/B50 (2)
	Operating temperature range [°C]	5 ÷ 30
	Driver	standard on/off (E)
	Power factor cos φ	>0,95
	Circuit load capacity	16 (B10), 26 (B16), 23 (C10), 37 (C16)
Mechanical data	Assembly	mounted in module ceilings
	Material	steel sheet
	Color	white
	Diffuser	SHM (hardened mat glass)
	Impact resistant	IK08
	Dimensions [mm]	1196 x 596 x 67

Mounting hole [mm]

1180 x 580



A graph of light



Accessories

Index 6BZBO60980 Name Handle for pane opening



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023