

Product: AGAT CLEAN NO FRAME LED 10400 SHM E IP65 840 / 1200X600 Index: 19.4054.2221.34



Description

Luminary designed to module suspended ceilings, equipped with highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminary body. Luminary recommended for: operating and treatment rooms, as well as intensive care units.


Product information	CategoryClean luminaires - receFamilyAGAT CLEAN NO FRANNameAGAT CLEAN NO FRANIndex19.4054.2221.34IndexIndex	
Light and electrical data	Light source Luminous flux LED [Im] LED power [W] Luminaire luminous flux [Im] Power of luminaire [W] Luminaire's light efficiency [Im/W] Color of the light [K] CRI SDCM (LED sources) Beam angle [°] Protection against electric shock	LED 10468 53,2 8426 56,3 149,7 4000 >80 3 (C0-C180) / (C90-C270) - 109,6° / 109,6° I
	Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] Driver Power factor cos φ Circuit load capacity	IP65 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) 5 ÷ 30 standard on/off (E) >0,95 16 (B10), 26 (B16), 23 (C10), 37 (C16)
Mechanical data	Assembly Material Color Diffuser Impact resistant Dimensions [mm]	mounted in module ceilings steel sheet white SHM (hardened mat glass) IK08 1196 x 596 x 67

Mounting hole [mm]

1180 x 580



A graph of light



Accessories

Index 6BZBO60980 Name Handle for pane opening



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023