

Product: RUBIN CLEAN CORNER INOX LED 2200 SHM KR E IP65 830

Index: 19.4061.1111.20



Description

Hermetic luminary dedicated for clean rooms, and other health service structures. Luminary to be surface mounted or in the walls and ceilings corners. Luminary equipped in highly efficient LED sources. Its optical system is equipped with the diffuser made from mat hardened glass. Luminary cover is made from INOX steal. The screws are flushed with the luminary surface to reduce the number of elements and to facilitate its cleaning. Luminary high hermetic feature is provided by silicon seals placed among the elements. Luminary equipped with the protective mesh made from the INOX steal.

Product information

Category	Clean luminaires - surface
Family	RUBIN CLEAN CORNER INOX LED
Name	RUBIN CLEAN CORNER INOX LED 2200 SHM KR E IP65 830
Index	19.4061.1111.20














Light and electrical data

Light source	LED
Luminous flux LED [lm]	2203
LED power [W]	11,7
Luminaire luminous flux [lm]	1734
Power of luminaire [W]	12,6
Luminaire's light efficiency [lm/W]	137,6
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution - Imax=-45°
Protection against electric shock	1
Protection degree	IP65
Voltage	220240 V, 5060 Hz
Voltage Lifetime of LED sources [h]	220240 V, 5060 Hz 100000 (1) / 147000 (2)
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lifetime of LED sources [h] Lx/By	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2)
Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	100000 (1) / 147000 (2) L80/B10 (1) / L70/B50 (2) -25 ÷ 30

Mechanical data



Assembly	surface mounted on ceiling
Material	INOX steel
Color	gray
Diffuser	SHM (hardened mat glass)
Impact resistant	IK10
Dimensions [mm]	675 x 252 x 115



A graph of light

