

**Product:** RUBIN CLEAN LED 8800/800 PLX E IP65 840/BLEU / 620X620 TWO CIRCUIT

**Index:** 19.4067.2541.34



## Description

Surface mounted luminaire equipped in highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame. Luminaire recommended for: operating and treatment rooms, as well as intensive care units.

## Product information


|          |  |
|----------|--|
| Category | Clean luminaires - surface   |
| Family   | RUBIN CLEAN LED  |
| Name     | RUBIN CLEAN LED 8800/800 PLX E IP65 840/BLEU / 620X620 TWO CIRCUIT |
| Index    | 19.4067.2541.34  |



## Light and electrical data

|   |  |
|---|--|
| Light source                              | LED                                    |
| Luminous flux LED [lm]                    | 9130                                   |
| LED power [W]                             | 46,8                                   |
| Luminaire luminous flux [lm]              | 6850                                   |
| Power of luminaire [W]                    | 49,1                                   |
| Luminaire's light efficiency [lm/W]       | 139,5                                  |
| Color of the light [K]                    | 4000/blue color                        |
| CRI                                       | >80                                    |
| SDCM (LED sources)                        | 3                                      |
| Beam angle [°]                            | (C0-C180) / (C90-C270) - 105° / 104,8° |
| Photobiological risk class (IEC/EN 62471) | RG0                                    |
| Protection against electric shock         | I                                      |
| Protection degree                         | IP65                                   |
| Voltage                                   | 220..240 V, 50..60 Hz                  |
| Lifetime of LED sources [h]               | 60000                                  |
| Lx/By                                     | L70/B50                                |
| Operating temperature range [°C]          | 5 ÷ 30                                 |
| Driver                                    | standard on/off (E)                    |
| Circuit load capacity                     | 7 (B10), 12 (B16), 12 (C10), 19 (C16)  |

## Mechanical data



|                  |                            |
|------------------|----------------------------|
| Assembly         | surface mounted on ceiling |
| Material         | steel sheet                |
| Color            | white                      |
| Diffuser         | PLX (PMMA opal)            |
| Impact resistant | IK04                       |
| Dimensions [mm]  | 620 x 620 x 78             |

## A graph of light

