

Product: RUBIN CLEAN LED CRI95 10800 MICRO-PRM E IP65 940 / 1220X620MM

Index: 19.4075.1641.34



Description

Luxiona Poland as the only company in Europe has obtained CRI>95 for its luminaires (it provides high level of R9 and R13 that faithfully render the color of blood and tissue). Luminary recommended for operating theatres - lighting that is applied should faithfully render the color of blood, tissue, and skin (R9 responsible for rendering „deep red” color, and R13 responsible for rendering „light orange” color). Surface mounted luminary equipped in highly efficient LED panels. Luminary body made from steel sheet, powder coated in white. Diffusers and optical systems in aluminum frame.

Product information

Category	Clean luminaires CRI95
Family	RUBIN CLEAN LED CRI95
Name	RUBIN CLEAN LED CRI95 10800 MICRO-PRM E IP65 940 / 1220X620MM
Index	19.4075.1641.34



Light and electrical data

Light source	LED
Luminous flux LED [lm]	11750
LED power [W]	72
Luminaire luminous flux [lm]	8724
Power of luminaire [W]	73,5
Luminaire's light efficiency [lm/W]	118,7
Color of the light [K]	4000
CRI	>95
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 89° / 89°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	9 (B10), 15 (B16), 15 (C10), 24 (C16)

Mechanical data



Assembly	surface mounted on ceiling
Material	steel sheet
Color	white
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Dimensions [mm]	1220 x 620 x 78

A graph of light

