

**Product:** AGAT CLEAN CLASS 5-6 NO FRAME LED 6500 MICRO-PRM SH E IP65 830 KRG3K / 600X600

**Index:** 19.4082.1211.34



## Description

Luminaire dedicated for the clean rooms of increased cleanliness class ISO 5-6. Luminaire designed to module suspended ceilings, equipped with highly efficient LED panels. Luminaire body made from steel sheet, powder coated in white. Its characteristic feature is lack of aluminum frame what allows to exclude the unwished-for contamination in clean rooms. There are no visible elements joining the diffuser and the luminaire body.

## Product information

Category	Clean Class 3-9
Family	AGAT CLEAN CLASS 5-6 NO FRAME LED
Name	AGAT CLEAN CLASS 5-6 NO FRAME LED 6500 MICRO-PRM SH E IP65 830 KRG3K / 600X600
Index	19.4082.1211.34



## Light and electrical data

Light source	LED
Luminous flux LED [lm]	6314
LED power [W]	33,3
Luminaire luminous flux [lm]	4545
Power of luminaire [W]	34,8
Luminaire's light efficiency [lm/W]	130,6
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 88° / 91,8°
Protection against electric shock	I
Protection degree	IP65
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	100000 (1) / 147000 (2)
Lx/By	L80/B10 (1) / L70/B50 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	standard on/off (E)
Power factor cos φ	>0,95
Circuit load capacity	22 (B10), 34 (B16), 33 (C10), 54 (C16)

## Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	white
Diffuser	Micro-PRM SH (micro-prismatic diffuser PMMA with hardened glass)
Impact resistant	IK08
Weight [kg]	7,7
Dimensions [mm]	596 x 596 x 67

## A graph of light



## Accessories

Index 6BZBO60980

Name Handle for pane opening

