

Product: X-LINE SLIM L-DOWN LED 5500 OPTICS-ASYM E 24 830 / L-1425MM S-1,5M

Index: 19.4090.4711.24



Description

The luminaire is made of aluminum profile. There is only lower half-space light distribution (L-DOWN). Comparing to the traditional X-Line LED, size of the luminaire has been reduced, and all construction has been closed in a narrow 48 mm profile, which gives now a more elegant form of the product. The X-Line Slim uses a PLX or Micro-PRM opal diffuser or lenses. All of this allows to manipulate light and create lighting systems, facilitating the creation of comfortable vision in the interiors and their aesthetic appearance. The X-Line Slim luminaire is designed for mounting on suspensions.

Product information

Category	Surface mounted luminaires
Family	X-LINE SLIM LED
Name	X-LINE SLIM L-DOWN LED 5500 OPTICS-ASYM E 24 830 / L- 1425MM S-1,5M
Index	19.4090.4711.24
















Light and electrical data

Light source	LED
Luminous flux LED [lm]	5526
LED power [W]	29
Luminaire luminous flux [lm]	4366
Power of luminaire [W]	30,5
Luminaire's light efficiency [lm/W]	143,1
Color of the light [K]	3000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	asymmetric light distribution - Imax=-20°
Protection against electric shock	1
Frotection against electric shock	I
Protection degree	IP40
	•
Protection degree	IP40
Protection degree Voltage	IP40 220240 V, 5060 Hz
Protection degree Voltage Lifetime of LED sources [h]	IP40 220240 V, 5060 Hz 100000 (1) / 147000 (2)
Protection degree Voltage Lifetime of LED sources [h] Lx/By	IP40 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B10 (2)
Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C]	IP40 220240 V, 5060 Hz 100000 (1) / 147000 (2) L80/B10 (1) / L70/B10 (2) 5 ÷ 30

Mechanical data






Assembly	surface mounted on slings
Material	aluminum
Color	anodised aluminum
Diffuser	OPTICS (optical system based on lenses)
Impact resistant	IK04
Dimensions [mm]	1425 x 48 x 70



A graph of light







Accessories

Index 6E1-500KWANK-3

Name SUSPENSION NEW TYPE-A+B 24 LENGHT 1,5M WIRE 3X SET



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT




Index 6E1-8670-B-1,5-3X

Name SUSPENSION NEW TYPE-F LENGHT-1,5 METER WIRE 3X 1-POINT




Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-500KWB24K-3

Name SUSPENSION NEW TYPE-A+E 24 LENGHT 1,5M WIRE 3X SET

