

Product: SNAKE V LED 2600 MICRO-PRM E 24 830 Index: 19.4093.3111.24




Description

Luminary equipped with the highly efficient LED source. Body made from aluminum profile. Optical system provides regular light distribution on diffuser. There are two kinds of diffusers available: opal and PMMA micro-prism. Luminary adapted to be mounted on suspensions or directly on a solid ceiling construction. The suspended version is equipped with the suspension system which is 1500 mm long, and has the smooth regulation of the suspension length. These lumi - naries may be dedicated to decorate the representative places such as: entrances, receptions, restaurants, halls, etc.

| Product information | | Category Architectural luminaires | | iminaires | |
|---------------------------|--|--|---|---|--|
| | | Family | SNAKE V LED | | |
| | | Name Index | SNAKE V LED SNAKE V LED 2600 MICRO-PRM E 24 830 19,4093,3111,24 | | |
| | | | | | |
| | | IIIUEX | 19.4093.3111.2 | | |
| | | | Œ | | |
| Light and electrical data | | Light source | | LED | |
| | | Luminous flux LED [lm] | | 2525 | |
| | | LED power [W | Ŋ | 13,3 | |
| | | Luminaire lum | inous flux [lm] | 1902 | |
| | | Power of luminaire [W] Luminaire's light efficiency [Im/W] Color of the light [K] | | 14,4 132,1 3000 | |
| | | | | | |
| | | | | | |
| | | CRI | | >80 | |
| | | SDCM (LED s | | 3 | |
| | | Beam angle [° | | (C0-C180) / (C90-C270) - 82,8° / 97,2° | |
| | | Protection against electric shock Protection degree Voltage Lifetime of LED sources [h] Lx/By Operating temperature range [°C] Driver Power factor cos φ Circuit load capacity | | I | |
| | | | | IP20 | |
| | | | | 220240 V, 5060 Hz | |
| | | | | 100000 (1) / 147000 (2) | |
| | | | | L80/B10 (1) / L70/B50 (2) | |
| | | | | °C] 5÷30 | |
| | | | | standard on/off (E) | |
| | | | | >0,95 | |
| | | | | 46 (B10), 74 (B16), 72 (C10), 115 (C16) | |
| Mechanical data | | Assembly | | irectly mounted to ceiling construction or urface mounted on slings | |
| | | | | luminum | |
| | | | | dised aluminum | |
| | | Diffuser | | Micro-PRM (micro-prismatic diffuser PMMA) | |
| | | Impact resista | nt IF | <04 | |
| | | Weight [kg] | 2 | ,78 | |
| | | Dimensions [n | nm] 5 9 | 90/590 x 63 x 74 | |
| | | | | | |

A graph of light



Accessories

Index 6E1-500KWAN1P-3

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-8670-B-1,5-3X Name SUSPENSION NEW TYPE-F

LENGHT-1,5 METER WIRE 3X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023