

### Product: SNAKE V LED 4400 MICRO-PRM E 24 830 Index: 19.4093.3211.24




## Description

Luminary equipped with the highly efficient LED source. Body made from aluminum profile. Optical system provides regular light distribution on diffuser. There are two kinds of diffusers available: opal and PMMA micro-prism. Luminary adapted to be mounted on suspensions or directly on a solid ceiling construction. The suspended version is equipped with the suspension system which is 1500 mm long, and has the smooth regulation of the suspension length. These lumi - naries may be dedicated to decorate the representative places such as: entrances, receptions, restaurants, halls, etc.

Product information	Category	Architectural luminaires
	Family	SNAKE V LED
	Name	SNAKE V LED 4400 MICRO-PRM E 24 830
	Index	19.4093.3211.24
		$\begin{array}{c} \hline \hline$
Light and electrical data	Light source	LED
	Luminous flux	IX LED [lm] 4406
	LED power [V	W] 23,4
		minous flux [lm] 3319
	Power of lumi	
		light efficiency [lm/W] 134,4
	Color of the li	
	CRI	>80
	SDCM (LED s	sources) 3
	Beam angle [	
	Protection aga	gainst electric shock I
	Protection de	egree IP20
	Voltage	220240 V, 5060 Hz
	Lifetime of LE	ED sources [h] 100000 (1) / 147000 (2)
	Lx/By	L80/B10 (1) / L70/B50 (2)
	Operating ten	mperature range [°C] 5 ÷ 30
	Driver	standard on/off (E)
	Power factor	· cos φ >0,95
	Circuit load ca	capacity <b>30 (B10), 48 (B16), 43 (C10), 70 (C16)</b>
Mechanical data	Assembly	directly mounted to ceiling construction or surface mounted on slings
	Material	aluminum
	Color	anodised aluminum
	Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
	Impact resista	tant IK04
	Dimensions [r	[mm] 590/590 x 63 x 74

# A graph of light



## Accessories

### Index 6E1-500KWAN1P-3

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-8670-B-1,5-3X Name SUSPENSION NEW TYPE-F

LENGHT-1,5 METER WIRE 3X 1-POINT



#### Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



#### Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023