

Product: SNAKE V LED 5200 MICRO-PRM E 24 840 Index: 19.4093.4321.24




Description

Luminary equipped with the highly efficient LED source. Body made from aluminum profile. Optical system provides regular light distribution on diffuser. There are two kinds of diffusers available: opal and PMMA micro-prism. Luminary adapted to be mounted on suspensions or directly on a solid ceiling construction. The suspended version is equipped with the suspension system which is 1500 mm long, and has the smooth regulation of the suspension length. These lumi - naries may be dedicated to decorate the representative places such as: entrances, receptions, restaurants, halls, etc.

Product information	Category Archited	ctural luminaires
	Family SNAKE	VLED
	-	V LED 5200 MICRO-PRM E 24 840
	Index 19.4093	.4321.24
Light and electrical data	Light source	LED
	Luminous flux LED [lm]	5234
	LED power [W]	26,6
	Luminaire luminous flux	
	Power of luminaire [W]	28,2
	Luminaire's light efficien	
	Color of the light [K]	4000
	CRI	>80
	SDCM (LED sources)	3
	Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°
	Protection against electr	
	Protection degree	IP20
	Voltage	220240 V, 5060 Hz
	Lifetime of LED sources	
	Lx/By	L80/B10 (1) / L70/B50 (2)
	Operating temperature	
	Driver	standard on/off (E)
	Power factor $\cos \varphi$	>0,95
	Power factor cos φ Circuit load capacity	>0,95 30 (B10), 48 (B16), 43 (C10), 70 (C16)
Mechanical data	•	
Mechanical data	Circuit load capacity	30 (B10), 48 (B16), 43 (C10), 70 (C16) directly mounted to ceiling construction or
Mechanical data	Circuit load capacity Assembly	30 (B10), 48 (B16), 43 (C10), 70 (C16) directly mounted to ceiling construction or surface mounted on slings
Mechanical data	Circuit load capacity Assembly Material	30 (B10), 48 (B16), 43 (C10), 70 (C16) directly mounted to ceiling construction or surface mounted on slings aluminum
Mechanical data	Circuit load capacity Assembly Material Color	30 (B10), 48 (B16), 43 (C10), 70 (C16) directly mounted to ceiling construction or surface mounted on slings aluminum anodised aluminum
Mechanical data	Circuit load capacity Assembly Material Color Diffuser	30 (B10), 48 (B16), 43 (C10), 70 (C16) directly mounted to ceiling construction or surface mounted on slings aluminum anodised aluminum Micro-PRM (micro-prismatic diffuser PMMA)

A graph of light



Accessories

Index 6E1-500KWAN1P-3

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-8670-B-1,5-3X Name SUSPENSION NEW TYPE-F

LENGHT-1,5 METER WIRE 3X 1-POINT



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT





Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023