

Product: MOSAIC LED PART2 1100/1800 PLX E 34 840 / BEZ ZASILACZA

Index: 19.4097.3728.34



## **Description**

System dedicated for  $600 \times 600$  module suspended ceilings. It has a module and segment construction that includes the simple element, the curve, +-shaped element, L-shaped element and T-shaped element. Combination of these elements provides unlimited possibilities of interior lighting arrangement. It is possible to combine the lighting functionallity and unique aesthetics of the interior. The location of segments can be altered any time be turning particular plaster boards. Owing to the color diffusers or LED RGB strips it is possible to obtain some extra color effects. The LED system can be easily dimmed what provides some extra energy savings.

#### **Product information**

Category	Architectural luminaires
Family	MOSAIC LED PART2
Name	MOSAIC LED PART2 1100/1800 PLX E 34 840 / BEZ ZASILACZA
Index	19.4097.3728.34
















# Light and electrical data

Light source	LED
Luminous flux LED [lm]	1152/1800
LED power [W]	7/13
Luminaire luminous flux [lm]	643/1004
Power of luminaire [W]	8/14
Luminaire's light efficiency [lm/W]	80/72
Color of the light [K]	4000
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 104,2° / 107,4°
B	
Protection against electric shock	1
Protection against electric shock Protection degree	IP20/40
	•
Protection degree	IP20/40
Protection degree Voltage	IP20/40 220240 V, 5060 Hz
Protection degree  Voltage  Lifetime of LED sources [h]	IP20/40 220240 V, 5060 Hz 60000
Protection degree  Voltage  Lifetime of LED sources [h]  Lx/By	IP20/40 220240 V, 5060 Hz 60000 L80/B10


#### Mechanical data



Assembly	mounted in module ceilings
Material	steel sheet
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	1
Dimensions [mm]	564 x 157 x 61



# A graph of light



### **Accessories**

Index 19.3025.2000.00

Name MOSAIC LED PART2 - Stencil

