

**Product:**EUROPANEL LED 8000 PLX EDD 34 IP20/54 940

**Index:** 19.4099.6443.34



## Description

Modern LED panel for installation in suspended ceilings or directly on the ceiling. Equipped with the highly efficient LED sources. Luminary body made from aluminum. PMMA opal diffuser. Colour of luminary - white. Luminary dedicated for the public use structure like offices, conference rooms, classrooms, lecture halls etc.

## Product information

Category	Recessed luminaires
Family	EUROPANEL LED
Name	EUROPANEL LED 8000 PLX EDD 34 IP20/54 940
Index	19.4099.6443.34



## Light and electrical data


Light source	LED
Luminous flux LED [lm]	7868
LED power [W]	65
Luminaire luminous flux [lm]	5696
Power of luminaire [W]	77
Luminaire's light efficiency [lm/W]	74
Color of the light [K]	4000
CRI	>90
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 115,4° / 107,6°
Photobiological risk class (IEC/EN 62471)	RG0
Protection against electric shock	II
Protection degree	IP20/54
Voltage	220..240 V, 50..60 Hz
Lifetime of LED sources [h]	70000 (1) / 56000 (2)
Lx/By	L70/B10 (1) / L80/B10 (2)
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,95
Circuit load capacity	12 (B10), 20 (B16), 20 (C10), 32 (C16)

## Mechanical data



Assembly	mounted in module ceilings, plasterboard ceilings or directly on the ceiling
Material	aluminum
Color	RAL 9016 (white)
Diffuser	PLX (PMMA opal)
Impact resistant	IK04
Weight [kg]	3,61
Dimensions [mm]	596 x 596 x 11


## A graph of light



## Accessories

Index 2C1A7392-34R

Name EUROPANEL / RIM COMPACT  
LED RECESSED ACCESSORIES  
34 / 600X600



Index 01ARTLUNCNW6

Name EUROPANEL / RIM COMPACT  
LED SURFACE ACCESSORIES  
STANDARD 34 / 600X600



Index 01ARTBLUNCNW6

Name EUROPANEL / RIM COMPACT  
LED SURFACE ACCESSORIES  
BASIC 34 / 600X600

