

Product: 34.244M TUNAS I SAME TANAS I SAME T

**1121MM TUNABLE WHITE** 

Index: 19.4157.1353.34



### **Description**

Luminaire made of aluminium profile. Compared to traditional X-Line G/K LED, the size has been reduced and the structure enclosed in a narrower profile, which allows a more elegant aspect of the product. X-Line Slim Recessed uses an antiglare louvre. All this makes it possible to adjust light and create lighting systems, easing the creation of a comfortable view of indoor spaces and their aesthetics. X-Line Slim Recessed is designed for built-in installation on ceilings. The luminaries are adjusted to be linked together with specially designed connectors, which provide great freedom in arranging elements of the system as well as great functionality. The luminaire is equipped with LED modules adjusted to regulate the color temperature of light in the range from 2700 K to 6500 K.

#### **Product information**

Category Recessed luminaires

Family X-LINE SLIM RECESSED LOW UGR LED LINE

Name X-LINE SLIM RECESSED LOW UGR LED 4200 RASTER DAISY-BLACK-WIDE EDD 34 827-865 LINE-1S / L-1121MM TUNABLE WHITE

19.4157.1353.34

Index














## Light and electrical data

Light source	LED
Luminous flux LED [lm]	3990÷4305 (2700÷6500 K)
LED power [W]	22,8
Luminaire luminous flux [lm]	3312÷3574 (2700÷6500 K)
Power of luminaire [W]	25,6
Luminaire's light efficiency [lm/W]	129÷140 (2700÷6500 K)
Color of the light [K]	2700 ÷ 6500
CRI	>80
SDCM (LED sources)	3
Beam angle [°]	(C0-C180) / (C90-C270) - 72,6° / 74,4°
Protection against electric shock	I
Protection degree	IP40
Voltage	220240 V, 5060 Hz
Lifetime of LED sources [h]	50000
Lx/By	L80/B10
Operating temperature range [°C]	5 ÷ 30
Driver	DIM DALI (EDD)
Power factor cos φ	>0,9
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)

#### Mechanical data





Assembly	mounted in plasterboard ceilings
Material	aluminum
Color	RAL 9016 (white)
Diffuser	RASTER (anti-glare louvre)
Impact resistant	IK04
Dimensions [mm]	1121 x 70 x 75
Mounting hole [mm]	1121 x 55



# A graph of light

