

Product: X-LINE LED 3250 MICRO-PRM EDD 24 830 LINE-1EL / L-1407MM Index: 19.4164.3213.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Category Surface mounted luminaires Family X-LINE LED LINE

Œ

LED

Name X-LINE LED 3250 MICRO-PRM EDD 24 830 LINE-1EL / L-1407MM

 $[P_{44}]$

IK₀₄

Index 19.4164.3213.24

Light and electrical data

Light source	LED	
Luminous flux LED [lm]	3158	
LED power [W]	17,1	
Luminaire luminous flux [lm]	2379	
Power of luminaire [W]	18,3	
Luminaire's light efficiency [lm/W]	130	
Color of the light [K]	3000	
CRI	>80	
SDCM (LED sources)	3	
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2	
Photobiological risk class (IEC/EN 62471)	RG0	
Protection against electric shock	I	
Protection degree	IP44	
Voltage	220240 V, 5060 Hz	
Lifetime of LED sources [h]	100000 (1) / 147000 (2)	
Lx/By	L80/B10 (1) / L70/B50 (2)	
Operating temperature range [°C]	5 ÷ 30	
Driver	DIM DALI (EDD)	
Power factor cos φ	>0,95	
Circuit load capacity	17 (B10), 28 (B16), 26 (C10), 41 (C16)	



Mechanical data	<u> </u>	Assembly	directly mounted to ceiling construction or surface mounted on slings
Α	I ↓H ⊨→ B	Material	aluminum
l ₄ ▶	U	Color	anodised aluminum
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
		Impact resistant	IK04
		Weight [kg]	3,5
		Dimensions [mm]	1407 x 63 x 74
A graph of light			g_{0}^{0} g_{0



Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT



Name X-LINE Clamp for line luminaires




Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-5X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 5X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023