

Product: X-LINE LED 2200 MICRO-PRM E 24 840 LINE-EL / L-567MM Index: 19.4167.1221.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Ρ	ra	bd	U	ct	ir	nf	or	m	ati	ioi	า
		Ju		υL					uu		

Category	Surface mounted luminaires
Family	X-LINE LED LINE
Name	X-LINE LED 2200 MICRO-PRM E 24 840 LINE-EL / L-567MM
Index	19.4167.1221.24
	$\underbrace{E}_{LED} \bigoplus $

Light and electrical data

Light source	LED		
Luminous flux LED [lm]	2283		
LED power [W]	11,7		
Luminaire luminous flux [lm]	1720		
Power of luminaire [W]	12,6		
Luminaire's light efficiency [lm/W]	136,5		
Color of the light [K]	4000		
CRI	>80		
SDCM (LED sources)	3		
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°		
Photobiological risk class (IEC/EN 62471)	RG0		
Protection against electric shock	I		
Protection degree	IP44		
Voltage	220240 V, 5060 Hz		
Lifetime of LED sources [h]	100000 (1) / 147000 (2)		
Lx/By	L80/B10 (1) / L70/B50 (2)		
Operating temperature range [°C]	5 ÷ 30		
Driver	standard on/off (E)		
Power factor $\cos \phi$	>0,9		
Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)		



Mechanical data	Птн	Assembly	directly mounted to ceiling construction or surface mounted on slings		
A	<u> </u> +'' ←+ B	Material	aluminum		
	U	Color	anodised aluminum		
		Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)		
		Impact resistant	IK04		
		Weight [kg]	1,65		
		Dimensions [mm]	567 x 63 x 74		
			90° 90° 75° 90° 60° 60° 45° 60° 45° 60° 45° 45° 45° 40° 40° 40° 40° 40° 40° 40° 40° 40° 40		



Accessories










Index 6E1-500KWAN1P-B Name SUSPENSION NEW TYPE-B 24 LENGHT 1,5M WITHOUT WIRE 1-POINT






Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT





Luminous flux tolerance +/- 10%. Power tolerance +/- 10%. Technical data may be changed. Photos of the luminaires may differ from reality. Date of last update: 24-01-2023