

Product: X-LINE LED 2200 MICRO-PRM E 24 830 LINE-S / L-562MM

Index: 19.4169.1211.24



Description

Light fitting made out of aluminium profile equipped with opal diffuser or MPRM and driver.X-LINE fittings are intended to be mounted on ceiling or pendants. The luminaries are adjusted to be linked together with specially designed links, which provide great freedom in arranging elements of the system as well as great functionality. In the family of X-LINE LED fittings modules of renowned brands are applied.

Product information

Category	Surface mounted luminaires
Family	X-LINE LED LINE
Name	X-LINE LED 2200 MICRO-PRM E 24 830 LINE-S / L-562MM
Index	19.4169.1211.24















Light and electrical data

Light source	LED			
Luminous flux LED [lm]	2203			
LED power [W]	11,7			
Luminaire luminous flux [lm]	1659			
Power of luminaire [W]	12,6			
Luminaire's light efficiency [lm/W]	131,7			
Color of the light [K]	3000			
CRI	>80			
SDCM (LED sources)	3			
Beam angle [°]	(C0-C180) / (C90-C270) - 82,8° / 97,2°			
Photobiological risk class (IEC/EN 62471)	RG0			
Protection against electric shock	I			
Protection degree	IP44			
Voltage	220240 V, 5060 Hz			
Lifetime of LED sources [h]	100000 (1) / 147000 (2)			
Lx/By	L80/B10 (1) / L70/B50 (2)			
Operating temperature range [°C]	5 ÷ 30			
Driver	standard on/off (E)			
Power factor cos φ	>0,9			
Circuit load capacity	46 (B10), 74 (B16), 72 (C10), 115 (C16)			




Mechani	cal data
---------	----------

_			_	
		Δ		



Assembly	directly mounted to ceiling construction or surface mounted on slings
Material	aluminum
Color	anodised aluminum
Diffuser	Micro-PRM (micro-prismatic diffuser PMMA)
Impact resistant	IK04
Weight [kg]	1,65
Dimensions [mm]	562 x 63 x 74

A graph of light





Accessories

Index 6E1-500KWAN1P-3

Name SUSPENSION NEW TYPE-A 24 LENGHT 1,5M WIRE 3X 1-POINT



Index 6E1-9875-3-1,5

Name SUSPENSION NEW TYPE-C LENGHT-1,5 METER WITHOUT WIRE 1-POINT




Index 6E1-500KWAN1P-B

Name SUSPENSION NEW TYPE-B 24
LENGHT 1,5M WITHOUT WIRE 1POINT




Index 0E1XLL-SLED

Name X-LINE Clamp for line luminaires



Index 6E1-8670-B-1,5

Name SUSPENSION NEW TYPE-E LENGHT-1,5 METER WITHOUT WIRE 1-POINT



Index 6E1-9875-4-1,5-3X

Name SUSPENSION NEW TYPE-D LENGHT-1,5 METER WIRE 3X 1-POINT

